

V8 Series



Constant Current LED Driver

LED恒流驱动器

Features:

- Constant current driver
- Independent compact design
- Captured terminal screws
- High power factor
- high efficiency
- Protections: opencircuit, shortcircuit, overload, overtemperature
- SELV class II output

- 恒流驱动
- 超小体积，独立式紧凑型设计
- 螺丝锁紧大接线端子，方便多规格线接驳
- 高功率因数设计
- 高效率，温升低
- 输出开路，短路，过载和超温保护
- SELV和II类等级



Parameters:

Model No.	Input voltage	Max. output	Output current	Output voltage	Power factor	THD	Efficiency full load	No-load power	Ambient temperature	Max. casing temperature	Isolation	Dimensions LxWxH	Weight
型号	额定电压 (V)	功率 (W)	输出电流 (mA)	输出电压 (V)	功率因数 (λ)	总谐波 (%)	效率 (%)	空载功率 (W)	环境温度 ta (°C)	最大外壳温度 tc (°C)	隔离	尺寸 (mm)	重量 (g)
V8-25-350	220-240	25	350	36-72	0.95	<10	88	<0.5	-20...+50	80	SELV	142x50x24	130
V8-25-500	220-240	25	500	25-50	0.95	<10	87	<0.5	-20...+50	80	SELV	142x50x24	130
V8-25-700	220-240	25	700	18-36	0.95	<10	87	<0.5	-20...+50	80	SELV	142x50x24	130
V8-40-500	220-240	40	500	40-80	0.95	<10	90	<0.5	-20...+50	80	SELV	142x50x24	130
V8-40-700	220-240	40	700	29-57	0.95	<10	89	<0.5	-20...+50	80	SELV	142x50x24	130
V8-40-1050	220-240	40	1050	19-38	0.95	<10	89	<0.5	-20...+50	80	SELV	142x50x24	130
V8-40-1400	220-240	40	1400	15-29	0.95	<10	88	<0.5	-20...+50	80	SELV	142x50x24	130
V8-60-1050	220-240	60	1050	29-57	0.95	<10	90	<0.5	-20...+50	80	SELV	166x52x24	130
V8-60-1400	220-240	60	1400	22-43	0.95	<10	89	<0.5	-20...+50	80	SELV	166x52x24	130